



NOZZLE SCHEDULE					
poc.	spec.	description	DN	PN (MPa)	note
1	A	Liquid phase/ drain	3/4"	2,5	NPT
2	B	Safety valve	*	2,5	NPT
3	C	Gas phase/Multiserv.	3/4"	2,5	NPT
4	D	Level gauge	Ø34	2,5	
5	E	Liquid phase filling	1 1/4"	2,5	NPT
6	F	Liquid phase**	2"	2,5	NPT
7	G,G'	Revision**	125	2,5	
8	B'	Safety valve	*	2,5	NPT

Volume (l.)	Dimensions (mm)							Masse (kg)
	L	B1	B2	B3	B	C1	C2	
1500	1500	100	600	-	100	-	-	373
1750	1700	100	800	-	100	-	-	405
2700	2480	100	1580	-	100	890	-	530
3600	3180	255	2000	-	120	965	580	650
4850	4260	775	2000	-	120	960	1630	820
6400	5500	650	3500	-	150	960	2880	1025
9100	7820	1060	2500	2500	150	2000	3000	1407
10000	8520	1100	2800	2800	150	2480	3000	1504

** Nozzle size acc. tank volume. (see CG.17.65.N/01.00.00-IZ);

** Option is stated in the contract (performance is possible only above-ground tanks).